

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 758 171 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
12.02.1997 Bulletin 1997/07

(51) Int Cl.⁶ H04L 7/033

(21) Application number: 96305520.7

(22) Date of filing: 26.07.1996

(84) Designated Contracting States:
DE FR GB

(72) Inventor: Chen, Dao-Long
Fort Collins, CO 80525 (US)

(30) Priority: 09.08.1995 US 513055

(74) Representative: Gill, David Alan
W.P. Thompson & Co.,
Celcon House,
289-293 High Holborn
London WC1V 7HU (GB)

(71) Applicant: SYMBIOS LOGIC INC.
Fort Collins, Colorado 80525 (US)

(54) Data sampling and recovery

(57) The invention provides for a circuit for detecting whether a reference clock signal (23) which can be one of n phase-shifted adjacent clock signals, of a phase-locked loop (PLL) (20) is aligned with incoming data (21), comprising a data sampler (26) for sampling bits of the incoming data (21) with each of the adjacent clock signals (23), wherein a first of the adjacent clock signals (23) clocks bits 0, $0+n$, $0+2n$, ... and a second of the adjacent clock signals clocks bits 1, $1+n$, $1+2n$, Also, a PLL circuit for recovering a clock signal from incoming data is provided, comprising a clock generator (22) for generating an odd number, n , of phase-shifted adjacent clock signals; a data sampler (26) for sampling the incoming data; a first pair of outputs from the sampler, for use in a phase detector (34) (along with a reference clock (25) of the adjacent clock signals and the incoming data), capable of producing an adjustment output. Another characterization is a method for recovering data in a PLL comprising the steps of: generating n phase-shifted adjacent clock signals for sampling bits incoming to the PLL; wherein a first of the adjacent clock signals clocks bits 0, $0+n$, $0+2n$, ..., and a second of the adjacent clock signals clocks bits 1, $1+n$, $1+2n$, Similarly, a third of the adjacent clock signals can be used to clock bits 2, $2+n$, $2+2n$, ..., as well as a fourth and fifth of the adjacent clock signals




FIG. 2

EP 0 758 171 A2

Description

The present invention relates to data sampling and recovery and in particular, but not exclusively, to the sampling and recovery of clock signals. The invention may also provide for data sampling/recovery in phase-locked loop (PLL)-type circuits as well as the use of PLLs for generating, aligning, and recovering data such as clock signals. More particularly, this invention can relate to an improved circuit for detecting whether a reference clock signal of a PLL is aligned with incoming data, an improved PLL circuit for recovering a clock signal from incoming data and an improved method of recovering data in a PLL.

Background information describing and illustrating PLLs currently in use for clock generation and synchronization can be found in an 1992 IEEE publication Circuits & Devices article entitled *Designing On-Chip Clock Generators* (pp. 32-36), authored by applicant Dr. Dao-Long Chen, as well as two reference texts: Electronic Communication Techniques, third edition, by Paul H. Young (see esp. all of chapter 10, and pp. 721-723); and Principles of CMOS VLSI Design, A Systems Perspective, second edition, by Neil H.E. Weste and Kamran Es-hraghian (see esp. pp. 334-336, and pp. 685-689).

PLL data recovery circuits are useful for recovering data and/or clock signals *after* transmission over a distance using, for example, fibre-optic (glass) cables. One recent PLL-type combination clock recovery circuit and demultiplexer circuit has been described (U.S. Patent No. 5,301,196) to operate at either half, or one-quarter, the data rate of a received data signal. The combination of circuits described is preferably designed for "the logic family of Gallium Arsenide (GaAs) MESFET differential current switched logic". The circuit combination includes a ring oscillator for generating either two phase-shifted clocks (0° and 90° for the half-speed circuit), or four phase-shifted clocks (0° , 45° , 90° , and 135° for the one-quarter speed circuit). The received data signal is used to edge-trigger either two (in the half-speed circuit), or four (in the one-quarter speed circuit) flip-flops to sample, respectively, either the two clocks (0° and 90°), or four clocks (0° , 45° , 90° , and 135°). The outputs of either the two, or four, flip-flops are then fed into an exclusive-OR gate, or a parity generator which has been connected in series with a loop filter and the ring oscillator.

PLL circuits used in today's high frequency systems are typically made using Silicon (Si) bipolar or GaAs (as preferred in the half- and quarter-speed circuits described above) integrated circuit technology. These PLL technologies are very limited in use due to high power consumption and/or high manufacturing cost. It is well understood that the manufacturing cost and/or power dissipation in MOS is generally lower than in comparable Si bipolar or GaAs circuits. These, among other reasons, make it desirable to build PLLs for high-performance communications systems using CMOS technology. However, building PLL components out of CMOS

that can reliably operate at such very high data rates (for example, at or in excess of 1-Gb/sec), has been beyond current CMOS technology capabilities.

The present invention seeks to provide for a data sampling and/or recovery method and apparatus having advantages over known such methods and apparatus.

According to one aspect of the present invention there is provided a circuit for determining whether a reference clock signal is coincident with incoming data, characterised by means for determining whether one of n phase-shifted adjacent clock signals of a phase-locked loop (PLL) coincident is with the incoming data, and comprising a data sampler for sampling bits of the incoming data with each of the adjacent clock signals, wherein a first of the adjacent clock signals clocks said bits $0, 0+n, 0+2n, \dots$, and a second of the adjacent clock signals clocks said bits $1, 1+n, 1+2n, \dots$.

The invention is advantageous in providing a method of recovering data in a phase-locked loop (PLL), that can be implemented using CMOS technology for high-speed serial data communication systems. Also, the invention can provide a circuit, for use in communication systems, capable of detecting whether a reference clock signal of a PLL is aligned with data incoming at a higher rate than the PLL's operating frequency, where the reference clock is one of n phase-shifted clock signals.

Advantageously, the circuit can include a first phase detector that operates on a first pair of outputs from the data sampler, and second phase detector that operates on a second pair of outputs from the data sampler, and so on. A phase adjustment output can be provided, as necessary, to a charge pump connected in series with a clock generator. Also provided is a PLL circuit for recovering a clock signal from incoming data having a clock generator for generating an odd number, n , of phase-shifted adjacent clock signals, and a data sampler for sampling the incoming data. A first pair of outputs from the data sampler may be used in a phase detector (along with a reference clock of the adjacent clock signals and the incoming data) for producing a phase adjustment output.

Advantageously said first phase detector further comprises first and second flip-flops, each of which operates with an output of said logic-AND device, an output of said first latch, and the other of said pair of adjacent clock signals, and second and third latches, each for sampling an output of each said flip-flop with the reference clock; said second and third latches for producing a phase adjustment output.

Also, a phase adjustment output of the circuit for a current-type charge pump connected in series with a loop filter and an n -stage voltage-controlled oscillator (VCO) having generated the adjacent clock signals.

Preferably, the circuit further comprises a second phase detector in series with a second charge pump, both of which are connected in parallel with said first phase detector and said current-type charge pump, and in which a second pair of outputs from said sampler

(wherein at least one of said second pair is different from said first pair of outputs) is used in said second phase detector along with a second reference clock signal of the adjacent clock signals and the incoming data.

Advantageously, a phase adjustment output of the circuit for a charge pump is connected in series with an $n=5$ -stage voltage-controlled oscillator (VCO) having generated the adjacent clock signals, and a third of the adjacent clock signals clocks said bits 2, $2+n$, $2+2n$, ..., a fourth of the adjacent clock signals clocks said bits 3, $3+n$, $3+2n$, ..., and a fifth of the adjacent clock signals clocks said bits 4, $4+n$, $4+2n$, ...

Preferably, the charge pump is a voltage-type charge pump connected in series with a low-pass loop filter and said VCO; and the circuit further comprises a first pair of outputs from said sampler for use in a first phase detector along with the reference clock signal and the incoming data.

According to another aspect of the present invention there is provided a method of recovering data in a phase-locked loop (PLL) characterised by the steps of generating n phase-shifted adjacent clock signals for sampling bits incoming to the PLL; wherein a first of said adjacent clock signals clocks said bits 0, $0+n$, $0+2n$, ..., and a second of said adjacent clock signals clocks said bits 1, $1+n$, $1+2n$, ...

Preferably, a third one of the adjacent clock signals can be used to clock bits 2, $2+n$, $2+2n$, Likewise, a fourth clock can be used to clock incoming bits 3, $3+n$, $3+2n$, ..., and a fifth clock signal can be used to clock incoming bits 4, $4+n$, $4+2n$, ...

Preferably, the method includes the steps of detecting whether a reference clock of said adjacent clock signals is aligned with said bits, and in the event of non-alignment, producing a phase adjustment output.

Advantageously, said step of detecting further comprises the steps of using a first pair of said sampled outputs, a reference clock of said adjacent clock signals, and said bits to produce said phase adjustment output, and the method further comprising the step of making any requisite phase adjustments to the PLL.

Also, the method may further comprise the step of detecting whether a second reference clock of said adjacent clock signals is aligned with said bits, and in the event of non-alignment, producing a second phase adjustment output to make any second requisite phase adjustment to the PLL.

Particular advantages exhibited by the various aspects of the present invention in providing an improved method for recovering data in a PLL and improved circuits for detecting whether a reference clock of a PLL is aligned with incoming data, as described herein, are as follows: (a) the clock generator and phase detection components of the PLL need not operate at the same high-speed as the incoming data; (b) by reducing the speed at which the PLL circuit components operate, integrated circuit technology typically reserved for lower speed circuits, can be used to implement the improved

method and circuits; (c) also, by reducing the speed at which PLL components must operate, power consumption of the implemented improved method and circuits will be reduced; (d) the reduced PLL operation frequency allows CMOS technology to be used, which can lower the overall cost of the integrated circuit ("chip") fabricated to implement the improved method and circuits; (e) more particularly, since the power dissipation in MOS is generally lower than in comparable bipolar circuits, using CMOS technology to implement the improved method and circuits will lower power consumption of the PLL; and (f) versatility--either bipolar or MOS technology can be accommodated.

The invention can also provide for a phase-locked loop (PLL) circuit for recovering a clock signal from incoming data, comprising a clock generator for generating an odd number, n , of phase-shifted adjacent clock signals, a data sampler for sampling the incoming data, and a first pair of outputs from said sampler for use in a first phase detector along with a reference clock of said adjacent clock signals and the incoming data wherein said phase detector is capable of producing an adjustment output for said clock generator.

Preferably, the clock generator comprises an n -stage voltage-controlled oscillator (VCO) arranged to generate said adjacent clock signals to operate at a trimmed frequency close to $1/n$ times the incoming data frequency, and said first phase detector further comprises a logic-AND device for operating on said first pair of outputs, one of which is inverted, and a first latch for sampling said reference clock with the incoming data.

Advantageously, the PLL circuit is such that a frequency detector sufficiently locks-in the PLL circuit to the frequency of said reference clock, said clock generator is an n -stage voltage-controlled oscillator (VCO), a first of said adjacent clock signals clocks said bits 0, $0+n$, $0+2n$, ..., a second of said adjacent clock signals clocks said bits 1, $1+n$, $1+2n$, ..., and a third of said adjacent clock signals clocks said bits 2, $2+n$, $2+2n$, ...

Further, said clock generator may comprise an n -stage voltage-controlled oscillator (VCO), said data sampler may comprise n latches, and said first phase detector may further comprise a logic-AND device for operating on said first pair of outputs, one of which having been inverted, a first latch for sampling said reference clock with the incoming data, and first and second flip-flops, each of which operates with an output of said logic-AND device, an output of said first latch, and another of said adjacent clock signals.

Yet further, the present invention provides for a circuit for detecting whether a reference clock signal, one of n phase-shifted adjacent clock signals, of a phase-locked loop (PLL) is aligned with incoming data, comprising a first pair of clocked outputs from a data sampler for use in a first phase detector along with the reference clock signal, and a second pair of clocked outputs from said sampler wherein at least one of said second pair is different from said first pair, is used in a second phase

detector along with a second reference clock signal of the adjacent clock signals.

Preferably, said first phase detector is capable of producing a first phase adjustment output for a first charge pump in series therewith, said second phase detector is capable of producing a second phase adjustment output for a second charge pump in series therewith, and said phase adjustment outputs are for a clock generator of the adjacent clock signals.

Advantageously, said first phase detector further comprises a logic-AND device for operating on said first pair of clocked outputs, one of which has been inverted, and a first latch for sampling the reference clock with the incoming data.

The circuit may further comprise a third pair of clocked outputs from said sampler, wherein at least one of said third pair is different from said second pair, and is used in a third phase detector along with a third reference clock signal of the adjacent clock signals and the incoming data.

Preferably, said third phase detector is capable of producing a third phase adjustment output for a third charge pump in series with a clock generator, and said first, second, and third phase detectors connected in parallel.

The new PLL circuits and new method described herein are particularly advantageous in that they make it possible to use, although not limited thereto, current CMOS fabrication technology to build PLL circuits for clock generation, alignment with incoming data, and recovery, as well as for data sampling and recovery.

The invention is described further hereinafter, by way of example only, with reference to the accompanying drawings in which:

Fig. 1 is a block diagram of a known simple PLL circuit 10 that uses a single clock pulse with a decision circuit 12, to export data from the PLL (along arrow 14);

Fig. 2 is a block diagram of a circuit embodying the present invention using, in this example, five adjacent clocks (labelled CLOCK1 - CLOCK5);

Fig. 3 is a timing diagram illustrating incoming data, five adjacent clocks, two clocked outputs, and the result of an AND operation of the two clocked outputs (one clocked output having, first, been inverted);

Fig. 4 is a schematic data sampler according to an embodiment of the invention whereby incoming data is sampled with five adjacent clocks;

Fig. 5 is a schematic diagram of a phase detector according to an embodiment of the invention, which can be implemented with Figs. 2 and 4, whereby two data sampler outputs are used with a reference CLOCK4 along with the incoming data for phase detection;

Figs. 6 and 7 are timing diagrams illustrating waveforms for two example conditions where Fig. 6

shows CLOCK4 lagging data 21 and Fig. 7 shows CLOCK4 leading the data; and

Fig. 8 is a schematic diagram illustrating an embodiment of the invention having three phase detectors in parallel, all feeding into a loop filter for phase correction.

A known simple PLL circuit 10 is shown in Fig. 1 (see IEEE Journal of Solid State Circuits, Vol. 23, No. 3, June 1988 *Multi-Gigabit-Per-Second Silicon Bipolar IC's for Future Optical-Fibre Transmission Systems*, esp. Figs. 1, 19, and 25) and uses a single clock pulse 15 generated by Voltage-Controlled Oscillator (VCO) 18, and a decision circuit 12 (which could be a master-slave D flip flop), to export data from the PLL (along arrow 14) for use, elsewhere, in a computer system. An integrated circuit component operating as a phase detector 16 is used, here, to send an output to charge pump 13 for charging VCO 18 either "up" or "down", as required. This allows for phase correction of the clock signal 15 (generated by VCO 18) to take place.

As can be readily seen in Fig. 2, an improved PLL circuit 20 has a clock generator 22 for generating, in this case, five phase-shifted adjacent clock signals 23 (as shown, also, in Fig. 3) which are fed via 24 into data sampler 26 for sampling bits of incoming data 21 which have entered the sampler along 21c (operation details will be described in connection with Fig. 4). Two of the five clocked outputs 28 (labelled D1 and D2 at 30, also shown in Figs. 3 and 4) enter phase detector 34 of PLL 20, along with two (CLOCK3, CLOCK4 at 25) of the five clocks 23 and input data (at 21b). The operation of phase detector 34 will be described in more detail in connection with Fig. 5. Phase adjustment outputs 35a and 35b enter charge pump 36 to either speed "up" or "down" the clock generator 22 so that phase adjustments can be made to the clock signals generated for the PLL. A loop filter 38 has been included. Clocked output data is exported along 32 from the PLL for use, elsewhere, in a computer system. Similarly, clock signals (in this example, five) can be exported from the PLL along 27 for use, elsewhere, in a computer system.

The clock generator is preferably a Voltage-Controlled Oscillator capable of generating *n* phase-shifted adjacent clock signals (or "clocks"). The two reference texts cited earlier, *Electronic Communication Techniques* and *Principles of CMOS VLSI Design, A Systems Perspective*, as well as the *Circuits & Devices* article *Designing On-Chip Clock Generators* describe various types of available VCOs and their design considerations. Preferably, a multivibrator or ring oscillator VCO can be used. One popular design of such oscillator comprises a current-starved ring oscillator, in which the charge and discharge currents are modulated by the control voltage (see, also, Fig. 5 of *Designing On-Chip Clock Generators*). Either of the two known types of charge pumps described in the *Designing On-Chip Clock Generators* article (a current-type or a voltage-

type) can be used in the Fig. 2 implementation. As will be described in further detail below, if a current-type charge pump is used and an "up" adjustment is needed to speed up the VCO (because the clocks are lagging behind), a switch is closed for one clock period to send a positively-flowing current from a current-source through the charge pump and into the VCO. The loop filter 38 can preferably be a low-pass filter. Using the analogy of water in a reservoir, a low-pass filter behaves like a big reservoir into which the charge pump can *pour*, or from which the pump can *take*. The output of the filter, represented by total reservoir water level, controls the frequency of VCO 22. The reservoir needs to be big enough so that any transient disturbances will not significantly change the water level.

Turning now to Fig. 3, a five-stage VCO can be built to generate five phase-shifted clocks. Each phase-shifted clock is delayed an amount equal to the incoming data period (T_{data} at 48). By way of example, in the event incoming data 21 is moving at a rate of 1-Gb/sec, T_{data} equals 1-nsec (i.e., the inverse of 1-Gb/sec). Thus, the frequency of such a five-stage VCO need only be 200 MHz (i.e., 1/5 of 1 GHz). A 200 MHz five-stage VCO can be implemented using known CMOS technology. Each of five clock phases generated by VCO 22 is used to sample the incoming data 21 in succession with data sampler 26 (see, also, Fig. 4), so that a total of five incoming bits 21 can be sampled during each 5-nsec clock period (T_{clock} at 46 in Fig. 3). Thus, an effective sampling rate of 1-Gb/sec, which is also the incoming data rate of this example, can be achieved for phase-locking.

Fig. 4 illustrates a preferred data sampler 26 for this five-clock example. Each phase-shifted clock, CLOCK1 through CLOCK5 shown at 41 - 45, samples successive incoming data bits 21 using a positive-edge triggered D flip-flop (or D latch). Five such D flip-flops are shown at 51 - 55. Incoming bits enter (along 21c) each flip-flop so that each of the adjacent clocks (41 - 45) can be used to clock a successive incoming bit. The clocked outputs are shown, respectively, along 61 - 65.

To ensure that each incoming data bit is strobed (or sampled) at the centre of the bit cells, it is important to control the timing of the phase-shifted clocks. In Fig. 3, the phase-shifted clocks are aligned with incoming data 21: The rising and falling data state changes occur in line with respective falling edges of the clocks. This is not necessarily always the case (as will be discussed in connection with Figs. 6 and 7). Therefore, a phase detector at 34 in Fig. 5 is used to check alignment of a reference clock (in this example, CLOCK4 at 44) generated by VCO 22. Turn, again, to Fig. 3. The state change of incoming data 21 between the rising edges of CLOCK1 (41) and CLOCK2 (42) is aligned with the falling edge of reference CLOCK4. If CLOCK4 (44) is sampled when incoming data 21 is between the rising edges of CLOCK1 and CLOCK2, it can be determined whether reference CLOCK4 (and, correspondingly, the other phase-shifted clocks) is leading or lagging the in-

coming data. Once this has been determined, an appropriate adjustment output can be sent to a charge pump 36 and on to VCO 22 (through a loop filter 38) as explained in connection with Fig. 2.

The preferred phase detector 34 in Fig. 5 uses input data 21b to sample (strobe) reference CLOCK4 (44) by operation of a D latch 70. Using a flip-flop 76 into which the output 68 of AND gate 67 is used for reset, CLOCK3 (43) samples the output 72 of D latch 70. Using a second flip-flop 78 into which the output 68 of AND gate 67 is used for reset, CLOCK3 (43) samples the inverted output 74 of D latch 70. Reference CLOCK4 is used to clock the output 77 of flip-flop 76 by operation of D latch 82 to produce an "up" phase adjustment output 35a. Reference CLOCK4 is additionally used to clock the output 79 of flip-flop 78 by operation of a second D latch 84 to produce a "down" phase adjustment output 35b.

The timing diagrams in Fig. 6 illustrate a situation where strobing CLOCK4 (44) between the rising edges of CLOCK1 (41) and CLOCK2 (42) results in a "1" (or "high") phase adjustment output 35a, indicating that the phase-shifted clocks are lagging (at 60a) the incoming data 21. In this case, the charge pump will pump the VCO "up" for one clock period (represented by T_{clock} at 46 in Fig. 3) to speed up the VCO. If the charge pump is a current-type, a first switch will close for one T_{clock} to send a positive current through the charge pump. If the charge pump is a voltage-type, a first switch will likewise close within the pump to increase the VCO oscillation voltage.

The timing diagrams in Fig. 7 illustrate a situation where strobing CLOCK4 (44) between the rising edges of CLOCK1 (41) and CLOCK2 (42) results in a "0" (or "down") phase adjustment output 35b, indicating that the phase-shifted clocks are leading (at 60b) the incoming data 21. In this case, the charge pump will pump the VCO "down" for one clock period (represented by T_{clock} at 46 in Fig. 3) to slow down the VCO. If the charge pump is a current-type, a second switch in the charge pump will close for one T_{clock} to send an oppositely-flowing current therethrough. If the charge pump is a voltage-type, a second switch will likewise close within the pump to decrease the VCO oscillation voltage.

Note that phase adjustment is done in coordination with the length of a clock cycle (T_{clock} at 46 in Fig. 3). In the event that making phase adjustments every T_{clock} is considered too long relative to the incoming data rate, it may be desirable or necessary to strobe the incoming data more often. Fig. 8 illustrates one implementation of the invention at 90 that includes a second phase detector 94 in series with a second charge pump 96 and a third phase detector 104 in series with a third charge pump 106. The outputs of the three charge pumps 36, 96, 106 are input into loop filter 38 (along 37, 97, 107) to adjust the clock generator 22 more frequently. Just as two clocks (CLOCK3 and a reference CLOCK4) are input via 25 into phase detector 34, two clocks (CLOCK4 and a reference CLOCK5 which is strobed for alignment

with incoming data 21d) can be input via 95 into phase detector 94. Similarly, two clocks (CLOCK1 and a reference CLOCK2 which is strobed for alignment with incoming data 21e) can be input via 105 into phase detector 104. Phase detector 94 uses two clocked outputs (D2, D3 along 92) and phase detector 104 uses clocked outputs (D4, D5 along 102). "Up" 98a and "down" 98b adjustment outputs from phase detector 94 will feed into charge pump 96. Likewise, "up" 108a and "down" 108b adjustment outputs from phase detector 104 will feed into charge pump 106.

Based upon the desired or required frequency of phase adjustments to a PLL clock generator, a circuit can be fabricated to strobe, in between the rising edges of two adjacent clocks, each of the generated phase-shifted clocks for alignment with incoming data 21. Such a circuit can be readily designed with five parallel phase detectors (corresponding to the five phase-shifted clocks generated in this example) using CMOS technology.

By way of additional examples, CMOS technology can also be used to implement the new method and PLL circuits of the invention using a clock generator having, theoretically, any number of stages for producing any number of phase-shifted clocks. A three-stage clock generator is built for data incoming at a rate of 1-Gb/sec would have to operate at 333.33 MHZ (or 1/3 times 1-Gb/sec). Likewise, a seven-stage clock generator built to recover data, also incoming at a rate of 1-Gb/sec, would need to operate at 142.86 MHZ, and so on. The data sampler for a three-stage VCO would include three incoming bit sampling devices. A data sampler for a seven-stage VCO would use seven incoming bit sampling devices, and so on. In any case, two adjacent clocked outputs could be input into a phase detector along with a reference clock and the incoming data for phase adjustment of the clock generator in accordance with principles discussed herein.

While certain representative embodiments and details have been shown for the purpose of illustrating the invention, those skilled in the art will readily appreciate that various modifications may be made to the invention without departing from the novel teachings or scope of this invention and so the present invention is not restricted to the details of the foregoing embodiments.

Claims

1. A circuit for determining whether a reference clock signal is coincident with incoming data, characterised by means for determining whether one of n phase-shifted adjacent clock signals of a phase-locked loop (PLL) (20) is coincident with the incoming data, and comprising:
 - a data sampler (26) for sampling bits of the incoming data with each of the adjacent clock signals, wherein a first of the adjacent clock signals

clocks said bits 0, $0+n$, $0+2n$, ..., and a second of the adjacent clock signals clocks said bits 1, $1+n$, $1+2n$, ...

2. A circuit as claimed in Claim 1, wherein the adjacent clock signals operate at a frequency less than the incoming data frequency; and
 - further comprising a first pair of outputs (D1, D2) from said sampler (26) having been produced from two of the adjacent clock signals for use in a first phase detector (34) along with the reference clock signal and the incoming data.
3. A circuit as claimed in Claim 2, wherein said first phase detector (34) is capable of producing a phase adjustment output for a charge pump (37) connected in series with a clock generator (22) having generated the adjacent clock signals to operate at a trimmed frequency close to $1/n$ times the incoming data frequency.
4. A circuit as claimed in Claim 2, wherein a pair of the adjacent clock signals, one of which is the reference clock (25), is used in said first phase detector (34); and
 - said first phase detector further comprises a logic-AND device (67) for operating on said first pair of outputs (D1, D2), one of which is inverted, and a first latch (70) for sampling the reference clock with the incoming data.
5. A phase-locked loop (PLL) circuit (20) for recovering a clock signal from incoming data (21), characterised by:
 - a clock generator (22) for generating an odd number, n , of phase-shifted adjacent clock signals;
 - a data sampler (26) for sampling the incoming data; and
 - a first pair of outputs (D1, D2) from said sampler (26) for use in a first phase detector (34) along with a reference clock of said adjacent clock signals and the incoming data wherein said phase detector (34) is capable of producing an adjustment output for said clock generator (22).
6. A circuit for determining whether a reference clock signal is coincident with incoming data, characterised by means for determining whether one of n phase-shifted adjacent clock signals of a phase-locked loop (PLL) (20) is coincident with the incoming data;
 - a data sampler (26) for providing a first pair of clocked outputs and for use in a first phase detector (34) along with the reference clock signal; and

a second pair of clocked outputs wherein from said sampler (26), wherein at least one of said second pair is different from said first pair, is used in a second phase detector (94) along with a second reference clock signal of the adjacent clock signals. 5

7. A method of recovering data in a phase-locked loop (PLL) (12) characterised by the steps of:
 - generating n phase-shifted adjacent clock signals for sampling bits incoming to the PLL; 10
 - wherein a first of said adjacent clock signals clocks said bits 0, $0+n$, $0+2n$, ..., and a second of said adjacent clock signals clocks said bits 1, $1+n$, $1+2n$, ... 15
8. A method as claimed in Claim 7, wherein n is an odd number, and further comprising the step of using a third of said adjacent clock signals to clock said bits 2, $2+n$, $2+2n$, ... 20
9. A method as claimed in Claim 7 or 8, wherein said step of generating comprises using an n -stage voltage-controlled oscillator operating at a trimmed frequency close to $1/n$ times the frequency of said bits; 25
 - using a fourth of said clock signals to clock said bits 3, $3+n$, $3+2n$, ..., and using a fifth of said clock signals to clock said bits 4, $4+n$, $4+2n$, ...; 30
 - detecting whether a reference clock of said adjacent clock signals is aligned with said bits; and
 - outputting the data from the PLL. 35
10. A method as claimed in Claim 9, wherein said step of detecting further comprises the steps of:
 - using a logic-AND device (67) on a first pair of said sampled outputs, one of which having first been inverted; 40
 - sampling said reference clock with said bits for input into each of a first and second flip-flops; and
 - sampling an output of each of said first and second flip-flops with said reference clock to produce any requisite phase adjustment output. 45

50

55




FIG. 1
PRIOR ART







FIG. 2



**FIG. 4****FIG. 5**





**FIG. 6****FIG. 7**

FIG. 8



THIS PAGE BLANK (USPTO)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 758 171 A3

(12) EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
26.11.1997 Bulletin 1997/48

(51) Int Cl.⁶: H04L 7/033

(43) Date of publication A2:
12.02.1997 Bulletin 1997/07

(21) Application number: 96305520.7

(22) Date of filing: 26.07.1996

(84) Designated Contracting States:
DE FR GB

(30) Priority: 09.08.1995 US 513055

(71) Applicant: SYMBIOS LOGIC INC.
Fort Collins, Colorado 80525 (US)

(72) Inventor: Chen, Dao-Long
Fort Collins, CO 80525 (US)

(74) Representative: Gill, David Alan
W.P. Thompson & Co.,
Celcon House,
289-293 High Holborn
London WC1V 7HU (GB)

(54) Data sampling and recovery

(57) The invention provides for a circuit for detecting whether a reference clock signal (23) which can be one of n phase-shifted adjacent clock signals, of a phase-locked loop (PLL) (20) is aligned with incoming data (21), comprising a data sampler (26) for sampling bits of the incoming data (21) with each of the adjacent clock signals (23), wherein a first of the adjacent clock signals (23) clocks bits 0, $0+n$, $0+2n$, ... and a second of the adjacent clock signals clocks bits 1, $1+n$, $1+2n$, Also, a PLL circuit for recovering a clock signal from incoming data is provided, comprising a clock generator (22) for generating an odd number, n , of phase-shifted adjacent clock signals; a data sampler (26) for sampling

the incoming data; a first pair of outputs from the sampler, for use in a phase detector (34) (along with a reference clock (25) of the adjacent clock signals and the incoming data), capable of producing an adjustment output. Another characterization is a method for recovering data in a PLL comprising the steps of: generating n phase-shifted adjacent clock signals for sampling bits incoming to the PLL; wherein a first of the adjacent clock signals clocks bits 0, $0+n$, $0+2n$, ..., and a second of the adjacent clock signals clocks bits 1, $1+n$, $1+2n$, Similarly, a third of the adjacent clock signals can be used to clock bits 2, $2+n$, $2+2n$, ..., as well as a fourth and fifth of the adjacent clock signals




FIG. 2



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 96 30 5520

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WO 95 14340 A (NAT SEMICONDUCTOR CORP) 26 May 1995 * page 4, line 13 - page 5, line 6 * * page 10, line 7 - page 11, line 8 * * page 12, line 1 - line 13 *	1,7-9	H04L7/033
X	EP 0 477 582 A (IBM) 1 April 1992 * page 2, line 14 - line 56 * * page 3, line 21 - page 4, line 17 *	1,7,8	
A	CLEMENTS S M ET AL: "Very high speed continuous sampling using matched delays" ELECTRONICS LETTERS, 17 MARCH 1994, UK, vol. 30, no. 6, ISSN 0013-5194, pages 463-465, XP000443603 * page 463, column 2 - page 464, column 2, last paragraph *	1-10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			H04L
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 25 September 1997	Examiner Van den Berg, J.G.J.
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 150 (12/92) (P/M/C/D)